

# Double door - sash lock

## Hardware set data sheet

Overhead door closing device with backcheck only ESD1500



- Power size: 2 to 4 adjustable by spring tension.
- Function: Closing speed, backcheck, latching.
- Cover: Radiused cover.
- Maximum door width: 1,100mm.
- Maximum door weight: 80kg.
- Qty: 2.

Mortice sashlock case ESD910



- Function: Latch bolt and deadbolt operation.
- Deadbolt projection: 21mm, single throw.
- Forend/strike material: Stainless steel.
- Forend type: Single.

Din lock intumescent pack ESD/INT-LOCK



- Intumescent pack to suit 72mm centres DIN lockcases.
- 1mm thickness.
- Consists of: 1 x lockcase & forend pad, 1 x strikeplate pad.
- Material: Mono-ammonium phosphate.
- Intumescent pack to be supplied with lockcase.

70mm Euro profile thumbturn cylinder ESD312170T



- Cylinder type: Key and turn cylinder.
- Keying function: Keyed to differ.
- Number of keys: 2 servant keys.

Escutcheon ESD - ESC/TURN



- Euro profile escutcheon 8mm.
- Fixing: 4 x 20mm screws.
- Material: Grade 304 stainless steel.

Stainless steel lever handle set on rose for interior doors ESD - E138F/42K-A2



- Material: Stainless steel grade 304.
- Bearing: Fixed/movable.
- Connection: Solid spindle with eccentric hole on both ends.
- Base: Stainless steel.
- Fixing: Bolt through and wood screws.

Flush bolt ESD326



- Material: Stainless steel.
- Function: Lever action.
- Fixing: Timber door screws.
- Qty 2 - (please note only 1 supplied if drop seals are in use)
- Fire rated products to be supplied with intumescents.

Fire door keep shut sign ESD902



- With lettering.
- 76mm diameter.
- Qty: 4.