

Leaf & half door - dead lock

10

Hardware set data sheet

Overhead door closing device with backcheck only **ESD1500**



- Power size: 2 to 4 adjustable by spring tension.
- Function: Closing speed, backcheck, latching.
- Cover: Radiused cover.
- Maximum door width: 1,100mm.
- Maximum door weight: 80kg.

Mortice deadlock case **ESD912**



- Function: Deadbolt operation.
- Deadbolt projection: 21mm, single throw.
- Forend/strike material: Stainless steel.
- Forend type: Single.

Din lock intumescent pack **ESD/INT-LOCK**



- Intumescent pack to suit 72mm centres DIN lockcases.
- 1mm thickness.
- Consists of: 1 x lockcase & forend pad, 1 x strikeplate pad.
- Material: Mono-ammonium phosphate.
- Intumescent pack to be supplied with lockcase.

70mm Euro profile thumbturn cylinder **ESD312170T**



- Cylinder type: Key and turn cylinder.
- Keying function: Keyed to differ.
- Number of keys: 2 servant keys.

Escutcheon **ESD - ESC/TURN**



- Euro profile escutcheon 8mm.
- Fixing: 4 x 20mm screws.
- Material: Grade 304 stainless steel.

300mm Stainless steel straight pull handle (exterior side) **ESD3616-300**



- Fixing: Pull handle fixing system no. BS13-B.

350mm Finger plate with radius corners **ESD324-300**



- Material: Stainless steel grade 304.
- Fixing: Drilled and countersunk supplied with wood screws.
- Radius corner.

Flush bolt **ESD326**



- Material: Stainless steel.
- Function: Lever action.
- Fixing: Timber door screws.
- Qty 2 - (please note only 1 supplied if drop seals are in use).
- Fire rated products to be supplied with intumescents.

Fire door keep locked sign **ESD901**



- With lettering.
- 76mm diameter.
- Qty: 4.